PacifiCrest

BRIGHT LIGHTS

Machine	Cut Pile
Yarn System	100% XTI® Type 6,6 nylon
Gauge	1/10th
Stitches per Inch	10.0
Finished Pile Height	.210"
Tufted Yarn Weight	30 Oz. per Sq. Yard
Yarn Construction	2 Ply Heatset
Dyeing Process	Piece Dye
Primary Backing	Woven Polypropylene
Secondary Backing	ActionBac®
Total Weight	Approximately 67 Oz. per Sq. Yard
Static Control	Built-in; Inherent in Fiber System
Soil Retardant	Royalguard Soil Resistance Treatment
Density Factor (D)	5,142
Weight Density (WD)	154,260
Flammability Test	Passes - Methenamine Pill Test DOC FF1-70
	Passes - Critical Radiant Flux ASTM E-648 - Class 1
	Passes - Smoke Chamber Test ASTM E-662
CRI +Plus Indoor Air Quality #	GLP 1360
Warranty	10 Year Fiber Wear Warranty & Life-of-the-Carpet Antistatic Warranty

RN 56412 MADE IN THE USA

PacifiCrest Mills is a clean air partner. This carpet is tufted and dyed in our state of the art, low environment impact, award- winning facility in Irvine, California. Contact PacifiCrest or your representative for details.

Antron · CERTIFIED BY SCIENTIFIC CERTIFICATION SYSTEMS · Environmentally Preferable Product · Carpet Fiber · SCS-EPP-01226

Environmentally Preferable Products are certified by Scientific Certification Systems as having a lesser or reduced effect on health and the environment when compared with competing products that serve the same purpose.

U.S. GREEN BUILDING COUNCIL MEMBER

LEED CREDIT LEED-CI v2.0	***CATEGORY DESCRIPTIONS***	***QUALIFYING DESCRIPTION***	**PTS**
EQ CREDIT 4.3 Environmental Quality	Low-Emitting Materials-Carpet	Low-VOC Approved by CRI Green Label Plus	1
MR CREDIT 5.1 Material Resource	Regional Materials 20%Manufatuctured Locally	100% of material cost for Projects within a 500 of Irvine CA	1