



KALLISTO (P0991)

Machine	Cut Pile
Yarn System	XTI® type 6,6 nylon
Gauge	1/10
Yarn Construction	2 Ply Heatset
Stitches Per Inch	10
Finished Pile Height	.210"
Tufted Yarn Weight	30 oz. per sq. yd.
Total Weight	Approximately 67 oz. per sq. yd.
Dyeing Process	Piece Dyed
Primary Backing	Woven Polypropylene
Secondary Backing	ActionBac®
Static Control	Built-in antistatic, warranted not to exceed 3.5kv
Soil Retardant	ROYALGUARD®
Density Factor (D)	5,142
Weight Density (WD)	154,260
Flammability Test	Passes Methenamine Pill Test DOC FF1-70 Passes Critical Radiant Flux ASTM E-648 – Class I Passes Smoke Chamber Test ASTM E-662
CRI Green Label Plus	GLP1360
Indoor Air Quality #	10-Year Limited Abrasive Wear Limited Lifetime Antistatic
Warranty	
RN 56412 MADE in U.S.A.	Yarn may be substituted due to industry fiber shortages.

PacifiCrest Mills is a clean air partner. This carpet is tufted and dyed in our state of the art, low environment impact, award-winning facility in Irvine, California. Contact PacifiCrest or your representative for details.

Environmentally Preferable Products are certified by Scientific Certification Systems as having a lesser or reduced effect on health and the environment when compared with competing products that serve the same purpose.



LEED CREDIT LEED-CI v2.0	CATEGORY DESCRIPTION	QUALIFYING DESCRIPTION	PTS
EQ CREDIT 4.3 Environmental Quality	Low-Emitting Materials Carpet	Low-VOC Approved by CRI Green Label +Plus	1
MR CREDIT 5.1 Material Resource	Regional Materials 20% Manufactured Locally	100% of material cost for projects within 500 miles of Irvine, CA	1