



LOFT (P0944)

Machine	Textured Cut Pile
Yarn System	STAINMASTER® BCF Nylon
Gauge	3/16
Yarn Construction	2 Ply Heatset
Stitches Per Inch	10.5
Finished Average Pile Height	.375"
Tufted Yarn Weight	25 oz. per sq. yd.
Approximate Total Weight	60 oz. per sq. yd.
Dyeing Process	Piece Dyed
Primary Backing	Woven Polypropylene
Secondary Backing	ActionBac®
Static Control	Built-in antistatic, warranted not to exceed 3.5kv
Soil Retardant	STAINMASTER®
Stain Retardant	STAINMASTER®
Density Factor (D)	2,880
Weight Density (WD)	86,400
Carpet Width	12'
Flammability Test	Passes Methenamine Pill Test DOC FF1-70 Passes Critical Radiant Flux ASTM E-648 – Class I Passes Smoke Chamber Test ASTM E-662
CRI Green Label +Plus	
Indoor Air Quality #	GLP1360
Warranty	Limited 10-Year Abrasive Wear, Limited 7-Year Stain Resistance, Limited 7-Year Soil Resistance, Limited Lifetime Antistatic
RN 56412 MADE in U.S.A.	Yarn may be substituted due to industry fiber shortages.

This carpet is intended strictly for residential use and warranty applies to residential installations only.

*PacifiCrest Mills is a clean air partner.
This carpet is tufted and dyed in our state of the
art, low environment impact, award-winning
facility in Irvine, California. Contact PacifiCrest
or your representative for details.*



LEED CREDIT LEED-CI v2.0	CATEGORY DESCRIPTIONS	QUALIFYING DESCRIPTION	PTS
EQ CREDIT 4.3 Environmental Quality	Low Emitting Materials Carpet	Low VOC Approved by CRI Green Label +Plus	1
MR CREDIT 5.1 Material Resource	Regional Materials 20% Manufactured Locally	100% of material cost for projects within 500 miles of Irvine, CA	2