



LOFT (P0944)

| | |
|-------------------------|---|
| Machine | Textured Cut Pile |
| Yarn System | STAINMASTER® BCF Nylon |
| Gauge | 3/16 |
| Yarn Construction | 2 Ply Heatset |
| Stitches Per Inch | 10.5 |
| Finished Pile Height | .375" |
| Tufted Yarn Weight | 25 oz. per sq. yd. |
| Total Weight | Approximately 60 oz. per sq. yd. |
| Dyeing Process | Piece Dyed |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | ActionBac® |
| Static Control | Built-in antistatic, warranted not to exceed 3.5kv |
| Soil Retardant | STAINMASTER® |
| Stain Retardant | STAINMASTER® |
| Density Factor (D) | 2,880 |
| Weight Density (WD) | 86,400 |
| Flammability Test | Passes Methenamine Pill Test DOC FF1-70 |
| CRI Green Label Plus | |
| Indoor Air Quality # | GLP1360 |
| Warranty | Limited 10-Year Abrasive Wear, Limited 7-Year Stain Resistance, Limited 7-Year Soil Resistance, Limited Lifetime Antistatic |
| RN 56412 MADE in U.S.A. | Yarn may be substituted due to industry fiber shortages. |

This carpet is intended strictly for residential use and warranty applies to residential installations only.

PacifiCrest Mills is a clean air partner. This carpet is tufted and dyed in our state of the art, low environment impact, award-winning facility in Irvine, California. Contact PacifiCrest or your representative for details.

Environmentally Preferable Products are certified by Scientific Certification Systems as having a lesser or reduced effect on health and the environment when compared with competing products that serve the same purpose.



| LEED CREDIT LEED-CI v2.0 | CATEGORY DESCRIPTION | QUALIFYING DESCRIPTION | PTS |
|--|--|--|-----|
| EQ CREDIT 4.3 Environmental Quality | Low-Emitting Materials Carpet | Low-VOC Approved by CRI Green Label +Plus | 1 |
| MR CREDIT 5.1 Material Resource | Regional Materials 20% Manufactured Locally | 100% of material cost for projects within 500 miles of Irvine, CA | 1 |