



**PENTHOUSE (P0941)**

Machine	Patterned Loop
Yarn System	Type 6,6 CF nylon
Gauge	1/8
Yarn Construction	2 Ply Heatset
Stitches Per Inch	12
Finished Average Pile Height	.312"
Tufted Yarn Weight	32 oz. per sq. yd.
Approximate Total Weight	67 oz. per sq. yd.
Dyeing Process	Piece Dyed
Primary Backing	Woven Polypropylene
Secondary Backing	ActionBac®
Pattern Repeat (W x L)	.5" x .703"
Static Control	Built-in antistatic, warranted not to exceed 3.5kv
Soil Retardant	Scotchgard™
Density Factor (D)	3,692
Weight Density (WD)	118,154
Carpet Width	12'
Flammability Test	Passes Methenamine Pill Test DOC FF1-70 Passes Critical Radiant Flux ASTM E-648 – Class I Passes Smoke Chamber Test ASTM E-662
CRI Green Label +Plus	
Indoor Air Quality #	GLP1360
Warranty	10-Year Limited Wear, 10-Year Limited Stain & Soil
RN 56412 MADE IN U.S.A.	Yarn may be substituted due to industry fiber shortages.

***This carpet is intended strictly for residential use and warranty applies to residential installations only.***

*PacifiCrest Mills is a clean air partner. This carpet is tufted and dyed in our state of the art, low environment impact, award-winning facility in Irvine, California. Contact PacifiCrest or your representative for details.*



LEED CREDIT LEED-CI v2.0	CATEGORY DESCRIPTION	QUALIFYING DESCRIPTION	PTS
EQ CREDIT 4.3 Environmental Quality	Low Emitting Materials Carpet	Low VOC Approved by CRI Green Label +Plus	1
MR CREDIT 5.1 Material Resource	Regional Materials 20% Manufactured Locally	100% of material cost for projects within 500 miles of Irvine, CA	2