



## PIERO (Po884)

Machine	Tip Sheared Patterned Loop
Yarn System	Antron® Legacy™ type 6,6 nylon
Gauge	1/8
Yarn Construction	Texture Ply
Stitches Per Inch	11.6
Finished Pile Height	.187”
Tufted Yarn Weight	34 oz. per sq. yd.
Total Weight	Approximately 71 oz. per sq. yd.
Dyeing Process	89.47% Piece Dyed, 10.53% Solution Dyed
Primary Backing	Woven Polypropylene
Secondary Backing	ActionBac®
Pattern Repeat (W x L)	.75” x Stripe
Static Control	Built-in antistatic, warranted not to exceed 3.5kV
Soil Retardant	DuraTech®
Density Factor (D)	6,545
Weight Density (WD)	222,545
Flammability Test	Passes Methenamine Pill Test DOC FF1-70 Passes Critical Radiant Flux ASTM E-648 – Class I Passes Smoke Chamber Test ASTM E-662
CRI Green Label +Plus	
Indoor Air Quality #	GLP1360
Warranty	10-Year Limited Abrasive Wear, Limited Lifetime Stain, Limited Lifetime Antistatic
RN 56412 MADE IN U.S.A.	Yarn may be substituted due to industry fiber shortages.

Antron® is a registered trademark of INVISTA for carpet fiber.  
DuraTech® is a registered trademark of INVISTA for soil resistant treatment.

*PacifiCrest Mills is a clean air partner. This carpet is tufted and dyed in our state of the art, low environment impact, award-winning facility in Irvine, California. Contact PacifiCrest or your representative for details.*



Environmentally Preferable Products are certified by Scientific Certification Systems as having a lesser or reduced effect on health and the environment when compared with competing products that serve the same purpose.



ENVIRONMENTAL OVERVIEW						
Carpet	Face Weight/oz	Post Industrial Fiber		Backing	Total Weight/oz	Total Green
Piero	34	24 oz.	71%	Standard	71	34%

LEED CREDIT LEED-CI v2.0	CATEGORY DESCRIPTION	QUALIFYING DESCRIPTION	PTS
EQ CREDIT 4.3 Environmental Quality	Low-Emitting Materials Carpet	Low-VOC Approved by CRI Green Label +Plus	1
MR CREDIT 5.1 Material Resource	Regional Materials 20% Manufactured Locally	100% of material cost for projects within 500 miles of Irvine, CA	1