



RAZZLE DAZZLE

Machine	Loop
Yarn System	100% XTI® Type 6,6 nylon
Gauge	1/10 th
Stitches per Inch	11.0
Finished Pile Height156"
Tufted Yarn Weight	32 Oz. per Sq. Yard
Yarn Construction	2 Ply Heatset
Dyeing Process	Piece Dye
Primary Backing	Woven Polypropylene
Secondary Backing	ActionBac®
Total Weight	Approximately 69 Oz. per Sq. Yard
Static Control	Built-in; Inherent in Fiber System
Soil Retardant	Royalguard Soil Resistance Treatment
Density Factor (D)	7,384
Weight Density (WD)	236,288
Flammability Test	Passes - Methenamine Pill Test DOC FF1-70 Passes - Critical Radiant Flux ASTM E-648 - Class 1 Passes - Smoke Chamber Test ASTM E-662
CRI +Plus Indoor Air Quality #	GLP 1360
Warranty	10 Year Fiber Wear Warranty & Life-of-the-Carpet Antistatic Warranty

RN 56412 MADE IN THE USA

PacifiCrest Mills is a clean air partner. This carpet is tufted and dyed in our state of the art, low environment impact, award- winning facility in Irvine, California. Contact PacifiCrest or your representative for details.



Environmentally Preferable Products are certified by Scientific Certification Systems as having a lesser or reduced effect on health and the environment when compared with competing products that serve the same purpose.



LEED CREDIT LEED-CI v2.0	CATEGORY DESCRIPTIONS	QUALIFYING DESCRIPTION	PTS
EQ CREDIT 4.3 Environmental Quality	Low-Emitting Materials-Carpet	Low-VOC Approved by CRI Green Label Plus	1
MR CREDIT 5.1 Material Resource	Regional Materials 20%Manufactured Locally	100% of material cost for Projects within a 500 of Irvine CA	1