



ROCK N' ROLL (Po843)

Machine	Patterned Cut & Loop
Yarn System	DSDN® nylon
Gauge	1/10
Yarn Construction	2 Ply Heatset
Stitches Per Inch	12.6
Finished Pile Height	.281"
Tufted Yarn Weight	34 oz. per sq. yd.
Dyeing Process	Solution Dyed
Primary Backing	Woven Polypropylene
Secondary Backing	E-LOK Laminate
Pattern Repeat (W x L)	12" x 10.25"
Static Control	Built-in antistatic, warranted not to exceed 3.5kv
Soil Retardant	Zonyl® 8779
Density Factor (D)	4,355
Weight Density (WD)	148,099
Flammability Test	Passes Methenamine Pill Test DOC FF1-70 Passes Critical Radiant Flux ASTM E-648 – Class I Passes Smoke Chamber Test ASTM E-662
CRI Green Label +Plus	
Indoor Air Quality #	GLP1322
Warranty	10-Year Limited Abrasive Wear, Limited Lifetime Antistatic
RN 56412 MADE in U.S.A.	Yarn may be substituted due to industry fiber shortages.

PacifiCrest Mills is a clean air partner. This carpet is tufted and dyed in our state of the art, low environment impact, award-winning facility in Irvine, California. Contact PacifiCrest or your representative for details.

Environmentally Preferable Products are certified by Scientific Certification Systems as having a lesser or reduced effect on health and the environment when compared with competing products that serve the same purpose.



ENVIRONMENTAL OVERVIEW										
Carpet	Face Weight/oz	Backing	Total Weight	Post Con. (oz)		Post Ind. (oz)		Rapid Renew (oz)		Total Green
Rock N' Roll	34	E-LOK Laminate	86.5 oz.	3-5	4%	26	30%	4.25	5%	39%

LEED Credit LEED-CI v2.0	CATEGORY DESCRIPTION	QUALIFYING DESCRIPTION	PTS
EQ CREDIT 4.3 Environmental Quality	Low-Emitting Materials Carpet	Low-VOC Approved by CRI Green Label +Plus	1
MR CREDIT 5.1 Material Resource	Regional Materials 20% Manufactured Locally	100% of material cost for projects within 500 miles of Irvine, CA	1