



SALERNO (Po890)

Machine	Tip Sheared Patterned Loop
Yarn System	Antron® Legacy™ type 6,6 nylon
Gauge	1/10
Yarn Construction	2 Ply Heatset
Stitches Per Inch	13.5
Finished Pile Height	.281”
Tufted Yarn Weight	38 oz. per sq. yd.
Total Weight	Approximately 75 oz. per sq. yd.
Dyeing Process	Piece Dyed
Primary Backing	Woven Polypropylene
Secondary Backing	ActionBac®
Pattern Repeat (W x L)	9.6” x 17.5”
Static Control	Built-in antistatic, warranted not to exceed 3.5kV
Soil Retardant	DuraTech®
Density Factor (D)	4,868
Weight Density (WD)	184,996
Flammability Test	Passes Methenamine Pill Test DOC FF1-70 Passes Critical Radiant Flux ASTM E-648 – Class I Passes Smoke Chamber Test ASTM E-662
CRI Green Label +Plus	
Indoor Air Quality #	GLP1360
Warranty	10-Year Limited Abrasive Wear, Limited Lifetime, Limited Lifetime Antistatic
RN 56412 MADE in U.S.A.	Yarn may be substituted due to industry fiber shortages.

Antron® is a registered trademark of INVISTA for carpet fiber.
DuraTech® is a registered trademark of INVISTA for soil resistant treatment.

PacifiCrest Mills is a clean air partner. This carpet is tufted and dyed in our state of the art, low environment impact, award-winning facility in Irvine, California. Contact PacifiCrest or your representative for details.



Environmentally Preferable Products are certified by Scientific Certification Systems as having a lesser or reduced effect on health and the environment when compared with competing products that serve the same purpose.



ENVIRONMENTAL OVERVIEW						
Carpet	Face Weight/oz	Post Industrial Fiber		Backing	Total Weight/oz	Total Green
Salerno	38	34.2 oz.	90%	Standard	75	45.6%

LEED CREDIT LEED-CI v2.0	CATEGORY DESCRIPTION	QUALIFYING DESCRIPTION	PTS
EQ CREDIT 4.3 Environmental Quality	Low-Emitting Materials Carpet	Low-VOC Approved by CRI Green Label +Plus	1
MR CREDIT 5.1 Material Resource	Regional Materials 20% Manufactured Locally	100% of material cost for projects within 500 miles of Irvine, CA	1