



**SUMMIT II**

|                                |  |
|--------------------------------|--|
| Machine .....                  | Level Cut & Loop   |
| Yarn System .....              | Du Pont XTI® Nylon   |
| Gauge .....                    | 1/10 <sup>th</sup>   |
| Stitches Per Inch .....        | 10.0   |
| Finished Pile Height .....     | .250"  |
| Tufted Yarn Weight .....       | 30 Oz. per Sq. Yard  |
| Yarn Construction .....        | 2 Ply Heatset  |
| Dyeing Process .....           | Piece Dye  |
| Primary Backing .....          | Woven Polypropylene  |
| Secondary Backing .....        | ActionBac®   |
| Total Weight .....             | Approximately 69 Oz. per Sq. Yard  |
| Pattern Repeat .....           | 1" x 1"  |
| Static Control .....           | Built-in; Inherent in Fiber System   |
| Soil Treatment .....           | Royalguard Soil Resist Treatment   |
| Density Factor (D) .....       | 4,320  |
| Weight Density (WD) .....      | 129,600  |
| Flammability Test .....        | Passes - Methenamine Pill Test DOC FF1-70<br>Passes - Critical Radiant Flux ASTM E-648 - Class 1<br>Passes - Smoke Chamber Test ASTM E-662 |
| CRI Indoor Air Quality # ..... | 13600678   |
| Warranty .....                 | 10 Year FiberWear & Life-of-the-Carpet Antistatic Warranties   |

RN 42032 MADE IN THE USA